Protector de columna ajustable

Protector de columna único fabricado con polietileno de baja densidad altamente flexible y resistente. Se suministra en cuatro secciones con travesaños de plástico que se pueden cortar para adaptarlos en obra, con tamaños de 200 mm a 700 mm. El protector de columna es de fácil montaje y no requiere fijaciones al suelo. Los tornillos de acero inoxidable se suministran como estándar.



Modelos

ARTÍCULOS / DESCRIPCIÓN



AG-CPU700 RAL 1003

Productos relacionados



X-PROTECT

Bolardos

Utilice nuestros bolardos X-Protect para proteger puertas, esquinas y maquinaria expuesta. Los bolardos negros y amarillos también atraen la atención del conductor de la carretilla elevadora y hace...

8 artículos



PROTECTOR DE COLUMNA

X-Protect Protector de columnas

Debe usar el protector de columnas cuando necesite proteger las columnas de su instalación de los daños por impacto. El diseño único presenta canales de aire especialmente formados que disipan las...

1 artículos



X-PROTECT

Protector vertical

Este protector vertical se adapta a todos los perfiles verticales de rack y patrones de ranuras comúnmente utilizados. Con su diseño de absorción de energía, distribuye las fuerzas de colisión sin...

3 artículos

Impact Protection



X-Protect is Safe

- ✓ Our impact protection products undergo rigorous testing at our state-of-the-art testing facility.
- ✓ With decades of experience in industrial safety, we've designed our impact protection to perform effectively in real-world conditions.
- ✓ We know safety and can guide you to the best solutions tailored to your specific needs.



- ✓ Quickly modify barrier specifications with minimal waste.
- ✓ Perform easy and cost-effective repairs at a component level.
- Quickly build strong integrated installations with few parts.

X-Protect is Sustainable

- Simple end of life dis-assembly, even after an accident.
- ✓ Single material components that are easy to recycle.
- Repairable by design, damaged or worn components are easily replaced extending the barrier's life.



Technical Information



X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Hand Rails



68 × 72 mm | 2 11/16" × 2 27/32" Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 × 220 mm | 4 9/16" x 8 21/32" Lenath:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Height: 350 - 1160 mm 13 13/16" -45 11/16" Width: 200 mm 7 7/8" in

Component Colours



RAL 1018




RAL 9011

X-Protect Standard Configurations



force depends on the C-C. More information is available upon request.





Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight 3600 kg/ 7930 lbs

Load
5020 J
8880 J
19960 J

Loaded weight 2700 kg/ 5940 lbs

Speed	Load
6 km/h 3.7 mph	3770 J
8 km/h 5 mph	6660 J
12 km/h 7.5 mph	14970 J


Loaded weight 2100 kg/ 4620 lbs


Speed	Load
6 km/h 3.7 mph	2930 J
8 km/h 5 mph	5180 J
12 km/h 7.5 mph	11670 J

Operating temperature









7 6700 J





The Floor Barrier can be used in combination with configurations: 3, 6, 8 & 9

DOWNLOAD OUR ASSEMBLY MANUALS

- 1. Bollards
- 2. Impact
- 3. Impact High
- 4. Double Impact Low
- 5. Double Impact High
- 6. Pedestrian
- 7. Pedestrian + Impact
- 8. Pedestrian + Impact High
- 9. Pedestrian +Double Impact
- 10. Pedestrian Gate
- 11. Column Guard